

Product Overview



PM3026GSMC V1 is a Web Smart Managed PoE Switch independently developed by UNIPOE. It provides 24*10/100/1000Mbps RJ45 ports and 2*1000Mbps SFP slots. Each RJ45 port supports MDI/MDIX automatic rollover and wire-speed forwarding. Ports 1-24 have the PoE power supply function and comply with IEEE 802.3af/at standards. They can be used as Ethernet power supply devices to automatically detect and identify

compliant power receiving devices and supply power to them through network cables. The storage and forwarding technology and dynamic memory allocation ensure that bandwidth is effectively allocated to each port.

PM3026GSMC V1 is easy to use and can flexibly expand home and office networks without limitation of power line layout. It is easy to manage and maintain and meets the requirements of different scenarios

Features

- Supports IEEE 802.3af/at standards;
- Automatic detection and identification standard PoE power receiving devices, intelligent power supply, does not burn non-standard PoE power receiving devices or common devices;
- Port power supply priority is supported to ensure continuous power supply for key nodes on the network;
- Supports the PD-ALIVE function;
- Supports IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control;
- Supports 802.1Q VLAN, Port VLAN, QoS, bandwidth control, and storm suppression;
- Supports port traffic statistics, port monitoring, cable detection, and loopback protection;
- Panel indicators monitor working status and assist in fault analysis;
- Intelligent identification of wire speed forwarding;
- Data exchange adopts store-and-forward mode;
- Operating temperature: 0°C ~ 40 °C.

Product Specifications

Model	PM3026GSMC V1	
Interface	24*10/100/1000Mbps RJ45 Ports 2*1000Mbps SFP Slots	
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1x, IEEE 802.1q, IEEE 802.1p, IEEE 802.1d, IEEE 802.1w, IEEE 802.3ad, IEEE802.3af, IEEE802.3at	
Network Media(Cable)	10BASE-T: UTP category 3, 5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 1000BASE-T: UTP category 5e, 6 cable(≤100m)	
MAC Address Table	8K, Auto-learning, Auto-aging	
Jumbo Frame	9K Byte	
Packet Buffer	4.1M bit	
Transfer Mode	Store-and-forward	
Switching Capacity	52Gbps	
Packet Forward Speed	39.69Mpps	
PoE Port	Port1~24	
PoE Port Output	Voltage: 55V DC 30W Max	
RJ45 PoE Power Supply	Mode A 1/2(+)/3/6(-)	
PoE Power Budget	250W	370W(Optional)
Power Input	280W	400W(Optional)
Input Voltage	AC 100-240V 50/60Hz	
Operating Temperature	0°C ~ 40 °C	
Storage Temperature	-40 °C ~70°C	
Operating Humidity	10% ~ 90% non-condensing	
Storage Humidity	5% ~ 90% non-condensing	
Dimensions(L*W*H)	440*207*44mm	
Fan Quantity	2	
Surge Protection	Differential mode ±2KV , Common mode ±4KV	
MTBF	>50000 hour	
Electrostatic Standard	Contact ±6KV , Air ±8KV	

Software Specification

Function menu	Functional description	Added
Basic	Login authentication and logout	
	Bilingual (Chinese-English Switching)	
	Port panel (dual color rate differentiator)	1000 m green 10 m / 100 m orange yellow
System configuration	Equipment information	Device name
		Device contact
		Location of equipment
	IP Address Setting	Static
		DHCP Client
		Support the DNS
	Web configuration	Web Timeout Setting
	User management	The password must contain at least six letters and digits
	The firmware update	Local upgrade
	Equipment management	Equipment to restart
Save Settings		
factory data reset		
Monitoring management	The port statistical	
	Cable testing	
	Ring network configuration	rlpp
Switch Configuration	Port configuration	Status
		Speed/Duplex/Flow Control
	Port mirror	Entrance/exit /ALL
	Port isolation	
	Static MAC	
	MAC filtering	
	MAC query	
MAC list	Categories display static/dynamic	
VLAN configuration	Member of the VLAN	
	VLAN configuration	Access, Trunk
QOS configuration	Port speed limit	
	The broadcast storm	
PoE configuration	The basic configuration	Enable/disable power supply
		Mandatory power supply
		Power limit
	PD Alive	
MCU Upgrade		

Ordering Information

Model	Product Information
PM3026GSMC V1	24GE(PoE)+2SFP Gigabit Web Smart PoE Switch