

Product Overview



PM236GTM V1 is a Fiber Managed Switch developed by UNIPOE, with 16*1000Mbps SFP slots, 8*1000Mbps Combo ports and 4*10Gbps SFP+ fiber modules and a Console port, providing complete security policies, perfect QoS policies and rich VLAN functions, easy to manage and maintain, meeting the networking and

access requirements of enterprises, communities, hotels, office networks and campus networks..

Product Features

- RJ45 supports automatic port flip (Auto MDI/MDIX);
- IEEE 802.3x full-duplex flow control and Backpressure half-duplex flow control;
- Panel indicators monitor working status and assist in fault analysis;
- Perfect security mechanism;
- Support for dynamic routing protocols;
- Highly reliable design, supporting traditional STP/MSTP/RSTP 3-layer link protection technology;
- Support static convergence and dynamic convergence (LACP) 2 convergence modes, effectively increase the link bandwidth, improve the reliability of the link, and at the same time can achieve load balancing, link backup;
- Flexible and convenient management and maintenance Supports various management modes, such as Console, Telnet, and SSH;
- Support WEB management, simple and efficient, convenient for installation and debugging of engineering and maintenance personnel;
- Supports file upload and download management through TFTP.

Product Specifications

Hardware Specifications

Model	PM236GTM V1
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1X, IEEE 802.1q, IEEE 802.1p, IEEE 802.1d, IEEE 802.1w, IEEE 802.3ad
Interface	16*1000Mbps SFP Slots 8*1000Mbps Combo Ports 4* 10Gbps SFP+ Slots 1*Console Port
Indicator	PWR(Green), LNK/ACT(Green), SYS(Green)
Network Media	10BASE-T: UTP category 3,4,5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 100BASE-TX UTP category 5e, 5 cable (≤100m) 1000BASE-FX: MMF, SMF 10GBASE-X: MMF, SMF
MAC Address Table	16K, Auto-learning, Auto-update
Jumbo Frame	12KBytes
Packet Buffer	12Mbit
Transfer Mode	Store-and-forward
Packet Forward Speed	95.23Mpps
Switching Capacity	128Gbps
Dimensions(L*W*H)	440*260*44mm
Fan	2 pcs
Power Supply	12V/5A
Power Input	100~240V AC, 50/60Hz
Operating Temperature	0°C ~ 40 °C
Storage Temperature	-40 °C ~ 70 °C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Surge Protection	Common mode ±4KV, Differential mode ±2KV
MTBF	>100000 hour
Electrostatic Standard	Contact ±6KV , Air ±8KV

Software Specification

L2 Features	MAC Address Table	MAC Address Size
		MAC Aging Time
		MAC Filter
		MAC Notification
	Basic Management	Console/Telnet/SSH
		Http/Https、SSL/TLS
		FTP/TFTP
		Syslog
		SNMP(v1/v2c/v3)、SNMP Trap
		SNTP/NTP
		CPU protect
		Software/Hardware watchdog
		Firmware Upgrade/Backup
		Ping/Traceroute
		Port Config
	Flow Control	
	EEE	
	MTU	
	CFM(802.1ag)	
	EFM OAM(802.3ah)	
	DDM	
	Storm Control	
	Port Isolation	
	Port Security	
	Virtual Cable Test	
	Discovery	LLDP(802.1ab)
		LLDP-MED
	Link Aggregation	Static
		LACP(802.3ad)
		Load Balance(src-mac/dst-mac/src-ip/dst-ip)
		Max groups and ports per group
	VLAN	VLAN(802.1Q 4K)
		Access/Trunk/Hybrid
		Private VLAN
		VLAN Filter
		MAC-based VLAN
		Protocol-based VLAN
		IP Subnet-based VLAN
		Voice VLAN
		GVRP/GMRP
		QinQ/Selective-QinQ/Flexible QinQ
		VLAN Translation/N:1 VLAN Translation
Guest VLAN		
Network Loop Detection	Loopback Detection	
	ERPS	
Spanning Tree	STP/RSTP/MSTP	
	MSTP Support 64 instance	
	BPDU Guard/Root Guard/BPDU Tunnel	
ARP	Static ARP	
	ARP Scanning Prevention	
	ARP Spoofing Prevention	
	ARP Guard	
	Gratuitous ARP	
	Dynamic ARP Inspection	

IPv4 Related Function	ICMP	ARP Quantity Control
		Anti ICMP Attack
		ICMP Rate Limit
		ICMP Unreachable Drop
	IP Forward	Static Route
		Route Aggregation
	Control Multicast	DCSCM
	Multicast VALN	Multicast VALN
	IGMP	IGMP SNOOPING V1/V2/V3
		Fast Leave
		IGMP Proxy
	DHCP	DHCP Server
		DHCP Client/BOOTP
		DHCP Relay
DHCP Snooping		
DHCP Option 82/43/60/61/67		
IPv6 Related Function	IPv6 Basic	IPv6 ND Snooping
	DHCPv6	DHCPv6 Server
		DHCPv6 Relay
		DHCPv6 Snooping
		IPv6 SAVI
		Security RA
	IPv6 Unicast Routing	Static Route
	IPv6 Multicast Routing	MLD v1/V2 Snooping
	IPv6 Features	SNMP over IPv6 Support
		HTTP over IPv6 Support
		SSH over IPv6 Support
		DNS over IPv6 Support
		IPv6 ping/traceroute Support
		IPv6 Telnet Support
		IPv6 Radius+ Support
		IPv6 Tacacs+ Support
		IPv6 SNTP/NTP Support
		IPv6 FTP/TFTP Support
		IPv6 IPSec Support
IPv6 ACL		
QoS(Quality Of Service)	Basic	Trust COS/DSCP
		Trust Port
	Scheduling	SP
		WRR
		WDRR
	PolicyMap Stream	Based on VLAN
		Based on COS/DSCP
		Aggregate PolicyMap
		Ingress PolicyMap
	Policing	CAR Stream Shaping(leak algorithm)
		Ingress Policing
	Rewrite	COS/802.1p Priority
		IP Precedence
		IPv4 DSCP/IPv6 DSCP
		drop-precedence
		internal-priority
		Ingress/Egress Rewrite
	Queuing	DSCP to DSCP mapping
		DSCP to DP mapping
		DSCP to Queue mapping

		COS to DP mapping
		COS to Queue mapping
ACL	IP-ACL	SIP/DIP
		IP Protocol
		IP Priority(DSCP,TOS, Precedence)
		TCP,UDP src,dst Port
	MAC-ACL	SRC/DST MAC
		VLAN
		COS
		Tag/Untag
	IP-MAC ACL	MAC-ACL and IP-ACL
	User-defined ACL	Base on user defined profile
ACL Features	Based on time period ACL	
	ACL on VLAN	
	Based on ACL Stream	
Security	802.1x	Port Based Authentication
		Support EAPoR
		MAC based Authentication
		Guest VLAN
	MAB	Based on Port Authentication
		Based on MAC Authentication
	MAC Address Count Limit	Based on Port
		Based on VLAN
	IP Address Count Limit	Based on Port
		Based on VLAN
	Access Management	Based on source mac and IP address
	Deny DoS Attack	TCP Flag
		TCP Fragment
IP Segment		
ICMP		
TACACS+	Standard Support	
Radius	Standard Support	
	Client, Support MD5	
SSL	Openssl 1.1.0	
Redundancy Related Function	MRPP	Compatiable ERRP
	ULPP	Uplink Protection Protocol
		Smart Link/Monitor Link
ULSM	Uplink State Monitor	
Flow Monitor Function	Mirror	Support one to one, multi to one
		Port based mirror, support ingress, egress, and both
		CPU based mirror
		Flow based mirror
		RSPAN

Ordering Information

Model	Product Information
PM236GTM V1	16G SFP+8G Combo+4*10G SFP+ L3 Fiber Managed Switch