

## Accessories

### ••• BM DS

## Remote LCD Display - DS

Applicable for MPPT solar charge controller:  
M2420/M2430/M2440/M4860  
M2420N/M2430N/M2440N/M4860N




This LCD display product has been used as the remote display unit for our charge controllers. You can check the working status and parameters in the screen, and set the system working parameters by key press operation.

### Key Figures


- Exclusive design for PV charge system monitoring
- Applicable for M Series controllers
- Easy fixture for remote monitoring
- 4 keys for multiple operation settings
- 2 ways of installation
- Inbuilt BT module for APP operation (optional)

### Installation methods

We provide 2 ways of wiring placement as shown in picture below for different installation uses. The user can either mount the screen directly on the wall, or fix it to the cabinet with wiring extended from the back of the screen.



### Dimensions



## APP Operation Bluetooth Module - BM




This BT module is an external device used for communication between the solar charge controller and mobile phone for APP operation. You can connect it to our charge controllers with RS485 port for APP operation function, and please notice that some of our models are with the BT module inside the controller for the same use.

### APP Use Quick Guide

Scan the QR code and download the APP "PVChargePro" to your mobile phone (Android & IOS versions)



PV Charge Pro



Google Play Store



IOS APP Store

Run the APP, and click on the up-right corner and choose the BT device ID, then you can get the APP applied with the charge controller.

