




## Freeze dryer

LGJ-12S/18S/30S heating in-situ freeze dryer series are small vertical freeze dryer machine. These models have shelf heating and programmable function. They are suitable for lab use or small-scale production, and they can meet requirements for most laboratories.

## **Features:**

- inch embedded integrated color touch-sereen, the operating system is a set of advanced Cortex-A8 processor, 128 MB capacity of high performance control system.
- ♦ The machine control system can save 40 freeze-drying scheme, each scheme can be set up 40 segments of temperature parameter values. Shelf has heating function.
- Operating system has manual operation and automatic operation, two workingmodes, to improve the selectivity of freeze-drying process.
- ♦ Have automatic alarm and protection function, equipment failure is easy to Judge.
- Have password protection function, to ensure the safe and reliable operation.
- ♦ Cascade refrigeration is optional, applied for -80°C machine.
- ◆ Optional remote monitoring and remote operation functions, convenient for user operation in different conditions.





## **Technical Specifications:**

recimical opecinications.						•				
Model		AE-LGJ-10		AE-LGJ-12/12S		AE-LGJ-18/18S			AE-LGJ-30S	
Specification	Unit	Standard	Top-pres s	Standar d	Top-press	Stan	dard	Top-press	Standard	Top-pres s
Freeze-drying area	m²	0.12	0.08	0.12	0.08	0.18	0.27	0.09	0.43	0.3
Cold trap temperature	С	<-56℃(nc	-loading), o	tion-80°C (no-loading)		$<$ -56 $^{\circ}\mathrm{C}$ (no-loading), option-80 $^{\circ}\mathrm{C}$ (no-loading)				
Vacuum degree	Pa	<10				<10				
Water-capture capability	kg/2 4h	3 4		3 4		6			8	
Material tray	mm	200mm,4 layers(6 layers as option)	180mm, 3 layers	200mm, 4 layers(6 layers as option)	180mm,3 layers	240m m,4 layers	240m m,4 layers	200mm,3 layers	280mm,7 layers	280mm,5 layers
Power	w	970		970		1400			2200	
Weight	kg	41		62		105			193	
Dimension	mm	615×450×370+(430m m as drum height)		580×500×720+(430m m as drum height)		630×580×970+(460mm as drum height)			1230×630×2190+(460 mm as drum height)	
Erial(Thickness:1 0mm)	L	1.2L(10m m)	8L(10m m)	1.2L(10 mm)	8L(10mm)	1.8L(1 0mm)	2.7L(1 0mm)	0.9L(10mm)	4.3L(10m m)	3L(10mm )
Exiling bottle	Piec e	Ф12mm: 920	Ф12mm: 560	Ф12mm : 920	Ф12mm: 560	Ф12m m: 1320	Ф12m m: 1980	Ф12mm: 990	Ф12mm: 3500	Ф12mm: 2470
	Piec e	Ф16mm: 480	Ф16mm: 285	Ф16mm : 480	Ф16mm: 285	Ф16m m:740	Ф16m m: 1110	Ф16mm: 555	Ф16mm: 1980	Ф16mm: 1380
	Piec e	Ф22mm: 260	Ф22mm: 165	Ф22mm : 260	Ф22mm: 165	Ф22m m: 360	Ф22m m: 540	Ф22mm: 270	Ф22mm: 960	Ф22mm: 675