



ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min.	Max.	Unit
Supply Voltage(Logic)	V _{DD} -V _{SS}	-0.3	4.0	V
Input Voltage	V _I	-0.3	V _{DD} + 0.3	V
Operating Temp.	T _{opr}	-20	70	°C
Storage Temp.	T _{stg}	-30	80	°C

MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size (W x H x T)	150.0 x 114.0 x 13.0	mm
Viewing Area (W x H)	118.0 x 88.8	mm
Active Area (W x H)	115.2 x 86.4	mm
Dot Pitch (W x H)	0.12 x 0.36	mm
Weight	Approx. 210	g

ELECTRICAL CHARACTERISTICS (V_{DD}=3.3V±0.3V)

Item	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input High Voltage	V _{IH}	--	0.9V _{DD}	--	V _{DD}	V
Input Low Voltage	V _{IL}	--	0	--	0.1V _{DD}	V
Supply Current (LED is turned on)	I _{DD}	V _{DD} = 3.3V	--	450	550	mA
Supply Current (LED is turned off)	I _{DD}	V _{DD} = 3.3V	--	170	200	mA

PIN CONNECTIONS (CN1/CN2)

Pin	Symbol	Level	Function
1	V _{SS}	0V	GND
2	V _{DD}	3.3V	Power supply
3	BL	H/L	LED backlight control signal H: LED on L: LED off
4	D/C	H/L	Data or command selection H: Display data L: Command
5	/WR	L	Write signal. Active "L".
6	/RD	L	Read signal. Active "L".
7	DB0	H/L	Data bus
8	DB1	H/L	
9	DB2	H/L	
10	DB3	H/L	
11	DB4	H/L	
12	DB5	H/L	
13	DB6	H/L	
14	DB7	H/L	
15	/CS	H→L	Chip enable signal. Active at falling edge.
16	/RST	L	Reset signal. Active "L".
17	NC	--	No connection
18	NC	--	No connection
19	NC	--	No connection
20	NC	--	No connection
21-22	NC	--	No connection
23-26	NC	--	No connection

BLOCK DIAGRAM

