

## MP-B38AT501LFA2-WT

5.0MP TUYA Smart WiFi Standalone 3.8 INCH Speed PT Dome Camera



Model	MP-B38AT501LFA2-WT
<b>Camera</b>	
Image Sensor	1/2.9" color CMOS
Effective Pixels	5.0MP
Synchronization	Internal
Code Format	H265
Code Rate	adaptive
Stream	Dual-stream
Frame Rate	Main code stream:2880*1616@25fps Auxiliary stream:704*576/352*288@25fps
Min. Illumination	0.05LUX/F1.2 color,0.005LUX/F1.2 WITH IR ON (BW)
Day & Night Mode	Color/B&W/Intelligent model
Electronic Shutter	Auto
White Balance	Auto
AGC	Auto

WDR	Digital WDR
DNR	3D DNR
IR LEDs	6PCS IR LEDs and 12PCS White LEDs Dual Light
IR Distance	IR Night Vision Distance 25M, Full Color Night Vision Distance 15M
<b>PT</b>	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	Max 30°/S
Tilt Speed	Max 30°/S
<b>Lens</b>	
Focal Length	3.6mm
Lens Megapixel	5 Megapixel fixed lens
<b>Functions</b>	
Motion Detection	Support (Low/Mid/High optional)
Human Detection	Support
Human Tracking	Support
Video Mask	4 windows can be built to mask your private area
IO Strobe Lights	Support (Red and Blue)
Alarm Linkage	The mobile detection alarm is pushed to the APP/Voice prompt alarm/IO red and blue strobe lights alarm linkage
Double Light source	When the infrared light triggers the alarm, the white light will turn on and the picture will switch to be colorful
Image Flip	Support
Electronic Amplification	6X
Audio	Built-in microphone and speaker, Support voice intercom
Storage	Built-in Micro SD card slot, Max 128G (Continuous recording/alarm recording)
Cloud Storage	Support
Web Access	Internet explorer 6.0 and above (Web Server embedded in device) browser
<b>NETWORK</b>	
Network Interface	1*RJ45 10M/100M Ethernet Port
WIFI	2.4G WiFi 802.11b/g/n
ONVIF	Support
Mobile Surveillance	iOS, Android (TUYA)
PC	No
<b>Interface</b>	
Power	1pcs DC female head
Ethernet	1pcs RJ45
Storage	1pcs Micro SD card
Antenna	2pcs integrated antennas

General	
Reset	Support
Power Supply	DC12V2A
Power Consumption	Max 6W
Language Support	ENG
Housing	Plastic Dome
Weather Proof	IP66
Lightning Protection	6KV
Working Temperature	-30 °C to +60 °C
Working Humidity	10%-90% RH (Non-condensing)