

MP-B105I300LF-WTA2

TUYA 4.0MP 1.5" Mini Smart WiFi SD I TF Card Plastic Speed Dome Camera



Model	MP-B105I300LF-WTA2
Camera	
Image Sensor	1/2.7" color CMOS
Effective Pixels	4.0MP
Synchronization	Internal
Code Format	H265
Code Rate	Adaptive
Stream	Dual-stream
Frame Rate	Main code stream:2560*1440@25fps/30fps Auxiliary stream:640x360@25fps
Min. Illumination	0.01LUX/F1.2 color,0.005LUX/F1.2 WITH IR ON (BW)
Day & Night Mode	Color/B&W/Intelligent model
Electronic Shutter	Auto
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR

IR Board	4PCS Infrared warm LEDs and 4PCS white LEDs
IR Distance	IR distance 25 meters, IR distance 10 meters for warm LEDs
PT	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	30°/S
Tilt Speed	30°/S
Lens	
Focal Length	3.6mm
Lens Megapixel	5 Megapixel fixed lens
Function	
Motion Detection	Support (Low/Mid/High optional)
Human Detection	Support
Human Tracking	Support
Alarm Linkage	The mobile detection alarm is pushed to the APP
Double Light Source	When the infrared light triggers the alarm, the white light will turn on and the picture will switch back to color
Image Rollovers	Support
Digital Zoom	Support
Audio	Built-in microphone and speaker, Support voice intercom
Storage	Built-in Micro SD card slot, Max 128G, timer capture
Cloud Storage	Support
Web Access	Support for substream preview
NETWORK	
Network Interface	1*RJ45 10M/100M Ethernet Port
WIFI	2.4G WiFi 802.11b/g/n,also support 5G
ONVIF	Support
AP	Support(It is only used to configure the network)
P2P	Support Max 3 users browsing at the same time
Mobile Surveillance	iOS, Android (TUYA)
PC	Web terminal stream preview
Interface	
Power	1pc DC female head
Ethernet	1pc RJ45
Storage	1pc Micro SD/TF card slot
Antenna	2pc integrated antennas
General	
Reset	Support
Power Supply	DC12V2A

Power Consumption	Max 5.5W
Language Support	ENG
Housing	Outdoor half-metal dome (Front cover metal)
Weather Proof	IP66
Lightning Protection	6KV
Working Temperature	-30 °C to +60 °C
Working Humidity	10%-90% RH (Non-condensing)